

Ref: ACDX-00027

PASSIVE 4CH VIDEO TRANSMISSION

Standard:	<ul style="list-style-type: none"> • AHD - 5 Mpx, • HD-CVI - 8 Mpx 4K UHD, • HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC
Device type:	Passive
Number of channels:	4 pcs Video
Video transmission range:	<ul style="list-style-type: none"> • 250 m @ 720p - UTP cat. 5e • 150 m @ 1080p - UTP cat. 5e • 400 m @ CVBS - PAL, NTSC - UTP cat. 5e
Coaxial socket voltage range 75Ω (CVBS):	1 Vpp
Attenuation:	<ul style="list-style-type: none"> • 4.43 MHz @ 0.73 dB • 11 MHz @ 1.24 dB • 21 MHz @ 2.16 dB • 38 MHz @ 3.35 dB • 42 MHz @ 3.54 dB • 67.5 MHz @ 3.72 dB
Isolation between inputs:	> -50 dB
Manufacturer / Brand:	DELTA
CMRR (dB @ 5MHz):	50 dB
Coaxial socket impedance:	75 Ω
Symmetrical socket impedance:	100 Ω
Coaxial socket type:	4 x BNC Straight socket
Symmetrical socket type:	Cable terminals / RJ-45 (8-pin, 4 pairs) Socket
Operation temp:	-50 °C ... 55 °C
Permissible relative humidity:	< 95 %
Weight:	0.105 kg
Dimensions:	120 x 30 x 62 mm