

IMT-ES0010RE

Loop powered sounder, IP65, red



Inim ES0010RE addressable loop-powered sounder unit in red enclosure. Connects directly to the loop. Weatherproof to IP67, suitable for outdoor installation. Up to 106 dBA (adjustable), 32 selectable tones, 9...60 Vdc, 4-41mA (depending on tone).

Information	
General information	
Order code:	IMT-ES0010RE
Product name:	Inim ES0010RE
Name on certification:	Inim ES0010RE
Function:	general purpose loop powered sounder, red
Conventional/Addressable/Wireless:	addressable with isolator
Protocol:	Inim Enea
Indoor/outdoor use:	outdoor
Protection category:	IP65
Use to following central panel(s):	IMT-SLI -2 (SmartLight) serie /Rev2.xx/; IMT-SLO -2 (SmartLoop) series /Rev2.xx/;
Power supply:	19...30 V DC
Stand by current consumption (at 24 V DC):	80 uA
Current consumption at alarm (at 24 V DC):	10...47 mA (depends on selected tone)
Sound level:	max. 94...106 dB(A)/1 m (dep. on tone)
Number of tones:	32
Frequency range:	400...2850 Hz
Brillance:	-
Loop powered:	yes
Others:	red; deep base; 2nd stage alarm control (with plus control line)
Dimensions:	98 mm (dia) * 104 mm
Operating temperature:	-5...+40 *C
Humidity:	no data