

IPMP - IP Management Platform

Complete Solution for Managing IP Services



Visonic's IPMP is a unique IP service management platform that enables alarm central stations and other security service providers to get maximum benefit from using IP technology for monitored premises.

- Cost effective all-in-one IP receiver solution for central monitoring stations
- Manages up to 20,000 accounts per server
- Optional hot standby redundancy
- Built-in message dispatcher sends notification to end-users via SMS, Email and MMS
- IPMP Lite edition for smaller central stations
- Out-of-the-box solution - Works with any monitoring station automation software that uses standard protocols; can be easily integrated with other automation software that uses non-standard protocols
- Remote access provided via a web-based graphical user interface
- Connection monitoring of connected systems (keep alive)
- When connected to Visonic's PowerLink and PowerMax®:
 - Remote system upgrades
 - PowerMax remote system configuration/programming
 - Advertisement/announcement delivery to end-users
 - Configurable, billed services



Visonic®

For a secure way of life

IPMP - Technical specifications and features

Choose the server that best suits your needs:



	IPMP (HP)	IPMP Lite (Dell)
Weight:	17.92kg (632.1oz)	6.80kg (239.86oz)
Dimensions (H x W x D):	4.32 x 42.62 x 69.22cm (1.7 x 16.78 x 27.25in)	9.26 x 31.4 x 34cm (3.65 x 12.36 x 13.39in)
Power supply wattage:	700W	235W
AC input voltage range:	100 to 240 VAC	90 to 264 VAC
AC input current range:	7.1 to 3.5A	4.5 to 2.25A
Operating temperature:	10° to 35°C (50° to 95°F)	10° to 35°C (50° to 95°F)
Storage temperature:	-40° to 70°C (-104° to 158°F)	-40° to 65°C (-104° to 149°F)
NIC supported data rates:	10/100/1000Mbps	10/100/1000Mbps
Redundant power supply:	YES	NO
Redundant fans:	YES	NO
Disk array:	RAID 0	N/A
Hot standby redundancy:	YES	NO
SMS/MMS notification messages:	YES	NO
Email notifications:	YES	YES
Number of accounts supported:	20,000	5,000
Server remote management "always available":	YES	NO
Configuration:	1U rack-space	Desktop

IP Receiver

Security system reporting protocols:	SIA/IP
Security system reporting encryption:	AES-128
Automation software communication:	MLR2 (CID/SIA) protocol over RS232 or TCP/IP
Security systems supervision (keep alive):	Configurable intervals
Notification dispatcher:	Using SMS, MMS or Email
Number of accounts supported (per server):	20,000 (IPMP)/5,000 (IPMP Lite)
Redundancy:	Hot standby
Events history per system:	256
Video verification reporting protocol:	PowerNet
Image storage:	Local or external network drive (FTP)

PowerLink and PowerMax management

Broadband remote programming of PowerMax systems:	Via GPRS
Configurable services:	Security, messaging, cameras, home devices (X-10)

Visonic and PowerMax are registered trademarks of Visonic Ltd. Other names are the property of their owners. Visonic reserves the right to change information or specifications without notice. VISONIC LTD. IPMP DATA SHEET ENG C-800574 (Rev.02)



Visonic[®]
For a secure way of life

•Head office Israel Tel (+972) 3 645 6789 •Spain Tel (+34) 91 659 3120 •U.S.A Tel +1 (860) 243 0833
 •Hong Kong Tel (+852) 2157 7147 •U.K. Tel (+44) 870 730 0800 •Germany Tel (+49) 211 600 6960
 •Nordic Tel (+47) 6758 0843 •Poland Tel (+48) 22 639 3436

For more information, visit us at: www.visonic.com or info@visonic.com