


## Grade 2 Magnetic Contacts


Full range of contacts at [www.cqr.co.uk](http://www.cqr.co.uk)

**FC508 MULTI** **FC508/WH or BR/MULTI/G2/EN**



- Body 20(dia) x 30mm, Face plate 22 x 33mm
- 4 Terminals
- Selectable resistors (A, B, D, E, I)
- Microswitch tamper
- Can be fitted in normal double pole configuration
- Can be used on double doors
- Operating gap - 9mm

**FC620** **FC620/WH**




- Flush pencil type contact
- 25(dia) x 33mm
- 4 core pre-wired
- Operating Gap - 15mm
- Collar for metal door
- EN50131-2-6 Grade 2 Environmental Class II

**FS610** **FS610/WH**




- Flush contact with surface adaptor
- 7(dia) x 26mm
- 4 core pre-wired
- Operating Gap - 10mm
- EN50131-2-6 Grade 2 Environmental Class II

**FC503** **FC503/WH or BR/G2**



- 9.5(dia) x 25mm
- 4 Core pre wired
- 15mm Operating gap
- Double pole or pre-restored - see resistor guide for type

**SC517 MULTI** **SC517/WH or BR/MULTI/G2/EN**



- 65 x 13.5 x 13mm
- 4 Terminals
- Selectable resistors (A, B, D, E, I)
- Microswitch tamper
- Can be fitted in normal double pole configuration
- Can be used on double doors
- Available white or brown
- Operating gap - 15mm

**SC570 MULTI** **SC570/WH or BR/MULTI**



- 85 x 25 x 20mm
- 6 Terminals
- Selectable resistors (A, B, D, E, F, H, I)
- Microswitch and wall tamper
- Operating gap - 27mm


**SC513** **SC513/WH or BR/4C**



SC513/WH or BR/4C

- 65 x 13.5 x 13mm
- Pre-wired
- Operating gap - 20
- Pre-restored - see resistor guide for type

**SC570** **SC570/WH or BR/EN**



SC570/WH or BR

- 85 x 25 x 20mm
- 6 Terminals
- Microswitch and wall tamper
- Operating gap - 27mm

### Resistor Table Guide

Type	Resistor Guide	Switch	Tamper
A	Honeywell, Microtech (Galaxy)	1K Ohms	1K Ohms
B	Scantronic, Cooper, Pyronix PCX, Texecom, Castle-Care Tec G3+	4K7 Ohms	2K2 Ohms
C	Guardall (Network 1 configuration) Two wire only	8K2 Ohms	8K2 Ohms
D	DSC	5K6 Ohms	5K6 Ohms
E	Gardtec	6K8 Ohms	4K7 Ohms

Type	Resistor Guide	Switch	Tamper
F	Bosch, DA Abacus	8K2 Ohms	3K9 Ohms
G	Castle Care-Tec	13K Ohms	1K Ohms
H	Europlex, MDT	2K2 Ohms	2K2 Ohms
I	Pyronix Matrix, GE / Aritech, HKC	4K7 Ohms	4K7 Ohms
J	Texecom	22K Ohms	10K Ohms



Independently Certified to EN50131

1 Grade 1 2 Grade 2 3 Grade 3

## Other Magnetic Contacts

Full range of contacts at [www.cqr.co.uk](http://www.cqr.co.uk)

### SC525

SC525/WH/4C



- Patio surface contact
- 38 x 15 x 10mm
- 4 Core pre-wired
- Operating Gap - 15mm
- EN50131-2-6 Grade 2 Environmental Class II

2

### SC517

SC517/WH or BR/G2



- 65 x 13 x 13mm
- 5 Terminals
- Operating Gap - 23mm
- Microswitch Tamper
- EN50131-2-6 Grade 2 Environmental Class II

2

### SC550

SC550/WH or BR



- Large surface contact
- 85 x 25 x 13mm
- 6 Terminals
- Operating Gap - 30mm
- Leaf spring tamper
- EN50131-2-6 Grade 2 Environmental Class II

2

### SC555

SC555//AL/4CX



- Aluminium surface contact
- 40 x 15 x 20mm
- 4 Core pre-wired
- Operating Gap - 150mm
- EN50131-2-6 Grade 2 Environmental Class II

2

### RS002

RS002/ALI/G2/AB



- Heavy Duty Roller Shutter
- Operating Gap: 50 mm
- Size: 175 x 50 x 13 mm
- High Quality Alloy Finish
- Pre-restored (A, B)
- 45cm & 1m Armoured Cable Lengths
- Other resistor value available  
- see resistor guide for type

2

### RS002

RS002/ALI



- Heavy duty roller shutter
- Operating gap: 50 mm
- Double pole
- Size: 175 x 50 x 15 mm
- High quality alloy finish
- 1 & 2 Reed versions available
- 45cm & 1m Armoured cable lengths
- Also available as pre-restored - see resistor guide for type

2

### GP001

GP001/AB/G2



- Heavy Duty Angled Contact
- Operating Gap: 45 mm
- Size: 85 x 27 x 26 mm
- High Quality Alloy Finish
- Pre-restored (A, B)
- 57cm Armoured Cable Lengths
- Other resistor value available  
- see resistor guide for type

2