Item Code: 100-071





Product Overview

Excel Category 6 Unscreened LSOH cables are manufactured and tested to the TIA/EIA 568-B.2-1, EN50173-1 and ISO/ IEC 11801 Category 6 specifications. Each cable consists of 8 colour coded polyethylene insulated conductors. These are twisted together to form 4 pairs with varying lay lengths. These pairs are then formed around a central X-shaped polyethylene filler, which assists in maintaining and enhancing the cable performance.

X Euroclass Dca-s2-d2-a1

The print legend on the cable now includes information regarding the DOP number, Test and Classification of the cable for traceability.

Product Specifications

| Faching | Values |
|---|--------|
| Feature | Values |
| Category | 6 |
| Overall screening | None |
| Conductor screening | None |
| Outer sheath colour | Violet |
| Reaction-to-fire class according to EN 13501-6 | Dca |
| Smoke development class according to EN 13501-6 | s2 |
| Euro class flaming droplets/particles according to EN 13501-6 | d2 |
| Euro class acidity according to EN 13501-6 | a1 |
| AWG-size | 23 |

Item Code: 100-071



| Specification core insulation | PE |
|--------------------------------|--|
| Core identification | Colour |
| Outer sheath material | Copolymer |
| Flame retardant | In accordance with EN 60332-1-2 and EN 50399 |
| Outer diameter approx. | 6.2 mm |
| Installation Temperature Range | 060 °C |
| Operating Temperature Range | -2075 °C |
| NVP value | 69 % |
| Conductor category | Class 1 = solid |
| Total number of cores | 8 |
| Stranding element | Pairs |
| Conductor surface | Bare |


Cable specifications

| Features | Values |
|-------------------------|-----------------------|
| Dielectric strength | 1200 V dc or 850 V ac |
| Maximum Pulling Load | 60N/6.1KgF |
| MBR during installation | 8x cable OD |
| MBR installed | 4x cable OD |

Item Code: 100-071



Cross-section diagram



Standards

| Applicable standard | Subject |
|--------------------------------|--|
| ISO/IEC 11801-1:2017 | Information technology - Generic cabling for customer premises: Part 1 General Requirements |
| IEC 61156-5:2009+AMD1:2012 CSV | Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification |
| EN 50173-1:2011 | Information technology. Generic cabling systems - General requirements |
| EN 50173-2:2007 + A1:2010 | Information technology. Generic cabling systems - Office premises |
| BS EN 50288-6-1:2013 | Multi-element metallic cables used in analogue and digital communication and control. Sectional specification for unscreened cables characterised up to 250 MHz |
| EN 50399:2011+A1:2016 | Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results |
| IEC 60332-1-2:2004 | Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame |
| ANSI/TIA 568-2.D | Balanced Twisted-Pair Telecommunications Cabling and Components Standards |
| IEC 60754-2:2011 | Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH |

Item Code: 100-071



| | measurement) and conductivity |
|--------------------------|--|
| IEC 61034-2:2005+A1:2013 | Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements |
| EN 50575:2014 + A1:2016 | Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements |
| RoHS | Restriction of Hazardous Substances - Compliant |

Part Number Table

| Part Number | Description |
|---------------|---|
| 100-071 | Excel Category 6 Cable U/UTP Dca LS0H 305m Box - Violet |
| 100-071-1000M | Excel Category 6 Cable U/UTP Dca LS0H 1000m Reel - Violet |
| 100-071-500M | Excel Category 6 Cable U/UTP Dca LS0H 500m Reel - Violet |
| 100-072 | Excel Category 6 Cable U/UTP Dca LS0H 305m Box - Green |
| 100-074 | Excel Category 6 Cable U/UTP Dca LS0H 305m Box - White |
| 100-074-1000M | Excel Category 6 Cable U/UTP Dca LS0H 1000m Reel - White |
| 100-074-500M | Excel Category 6 Cable U/UTP Dca LS0H White 500m Reel - White |
| 100-075 | Excel Category 6 Cable U/UTP Dca LS0H 305m Box - Orange |
| 100-103 | Excel Category 6 Dual Cable U/UTP LS0H 500m Reel - White |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

