

Section Public Address

Category Loudspeakers

Range Wall-mounting speakers / C94 Range

Code C94/15-T
C94/15-TN



Description 15 W, two-way, bass-reflex speaker unit

The **C94** range, made of ABS with a front metal grille, utilizes a compact two-way system guaranteeing high performances, wide dynamics, high fidelity sound reproduction and high voice intelligibility. These speaker units are equipped with an exclusive fully adjustable support bracket for easy installation, to cut costs and save installation time. The bracket may be attached to the wall prior to installing the loudspeaker and is provided with a safety cable. Connection to the loudspeakers is via plug in "Euroblock" connector and adjustment of loudspeaker output is made via screwdriver adjustable switch.

Technical data

Rated power	15 W
Adjustable power	15 - 7,5 - 4 - 2 W
Impedance	8 Ω
Loudspeakers	1 woofer + 1 tweeter (bass-reflex)
Sound pressure SPL (Pnom/1m)	100 dB
Sensitivity (1W/1m)	85 dB
Frequency response	100 ÷ 15.000 Hz
Dispersion angle @2kHz	120°
Mounting	Wall mounting bracket (supplied)
Colour	C94/15-T: WHITE (RAL 9016) C94/15-TN: BLACK
Dimensions	143 x 204 x 162 mm
Weight	1,5 kg

