CA2100P

CIAO WALL-MOUNT ENTRANCE PANEL FOR 1/2/4/8 BUT. S2

SB2

Ciao series modular entrance panel with die-cast aluminium front cover and nameplates with white LED backlighting. To be finished with 1/2/4/8 call buttons (art. CA9213, CA9210 CA9211 and CA9212 respectively), available to purchase separately. Featuring a smart button programming mode. Supplied with a surface-mount installation support. Entrance panel art. CA2100P can be used alongside up to 4 button modules art. CA2200P (both horizontally and vertically) to reach a maximum of up to 72 call buttons.

The technical specifications are subject to variations without warning.

CA2100P

CIAO WALL-MOUNT ENTRANCE PANEL FOR 1/2/4/8 BUT. S2

GENERAL DATA

Type:	Monoblock
Product height (inch):	6.73
Product width (inch):	3.88
Product depth (inch):	1.12
Product color:	Grey RAL 9006
Wall mounting:	Yes

COMPATIBLE SYSTEMS

Audio Simplebus 2 with power supply art. 1210:	Yes

AUDIO FEATURES

Microphone:	4 (ø), omnidirectional
Loudspeaker:	50mm (ø), 8 ohm, 0.2W

ELECTRICAL CHARACTERISTICS

Type of power supply:	Power supply from video door entry bus
Supply voltage:	27÷33VDC (bus)
Absorption in stand-by (W):	1.7
Maximum absorption (W):	7.6

HARDWARE FEATURES

Call type:	Push-buttons
Type of push-buttons:	Mechanical
Backlight color:	White
Terminals:	L L COM DO RTE C NO NC SE+ SE-
Removable terminals:	Yes
Number of inputs:	2
Number of exits:	1

SETTINGS

Loudspeaker volume:	Yes
Backlight brightness:	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection degree:	IP54
IK vandal-proof protection degree:	IK08

The technical specifications are subject to variations without warning.

Comelit
Passion.Technology.Design.

CA2100P

CIAO WALL-MOUNT ENTRANCE PANEL FOR 1/2/4/8 BUT. S2

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°K):	-13 ÷ 131
Operating humidity (RH max - %):	25 ÷ 75
Environmental class:	III
Compliance and Certifications:	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener:	Yes
Number of auxiliary relays:	1
Input for local door release button:	Yes
Door open signaling input:	Yes

Comelit
Passion.Technology.Design.

The technical specifications are subject to variations without warning.

CA2100P

CIAO WALL-MOUNT ENTRANCE PANEL FOR 1/2/4/8 BUT. S2

ACCESSORIES

CA2200P CIAO WALL-MOUNTED MODULE FOR 2/4/8/16 BUTTONS. S2
Ciao series button module with die-cast aluminium front cover and nameplates with white LED backlighting. To be finished with 2/4/8/16 call buttons (art. CA9210, CA9211, CA9212 and 2 x CA9212 respectively), available to purchase separately. Supplied with a surface-mount installation support. Can be used alongside up to 4 button modules (both horizontally and vertically).

CA9213 1 LARGE BUTTON FOR CIAO ENTRANCE PANEL

CA9210 2 DOUBLE-HEIGHT BUTTONS FOR CIAO ENTRANCE PANEL

CA9211 4 SINGLE BUTTONS FOR CIAO ENTRANCE PANEL

CA9212 4 DOUBLE BUTTONS FOR CIAO ENTRANCE PANEL

The technical specifications are subject to variations without warning.