



6601W

ICONA MONITOR, S2



Flush-mounted (in box Art. 6117) or wall-mounted (with bracket Art. 6620) colour monitor with 4.3" 16/9 screen, Full-Duplex hands-free audio and touch-sensitive controls. Allows adjustment of brightness level, contrast, audio volume and ringtone volume. Ringtones can be customised by selecting from the various melodies provided. Fitted as standard with a key button, enable/disable audio button with corresponding indicator LEDs and a further 7 programmable buttons for self-ignition, privacy service and other programmable functions. It is normally used for floor door call and call repetition management, and comes complete with 2 x 8-position DIP SWITCHES for user code programming and button programming. Equipped with riser distribution terminal Art. 1214/2C. The monitor can only be used in 2-wire Simplebus2 Colour systems. Dimensions 5.6"x5.7"x0.9".

AWARDS




6601W
ICONA MONITOR, S2
GENERAL DATA

Product height (inch):	5.79
Product width (inch):	5.61
Product depth (inch):	0.91
Product weight (oz):	1.1
Product color:	White RAL9003, base grey RAL7001
Material:	ABS, PMMA
Flush mounting:	Yes, with a dedicated accessory
Wall mounting:	Yes, with a dedicated accessory
Desk base-mounted:	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888C:	Yes
Audio/video Simplebus 2 with power supply art. 1210:	Yes
Simplebus 2 audio/video kit with power supply art. 1209:	Yes

DISPLAY FEATURES

Size (inches):	4.3
Aspect Ratio:	16:9
Resolution (pixels):	480x272

AUDIO FEATURES

Type:	Hands-free
Microphone:	6mm (Ø), omnidirectional
Loudspeaker:	40 (Ø) x 20 (H) mm, 8 ohm, 2W
Technologies implemented:	Full-duplex

ELECTRICAL CHARACTERISTICS

Type of power supply:	Power supply from video door entry bus
Supply voltage:	22÷34VDC (bus)
Maximum absorption (W):	10.8

HARDWARE FEATURES

Type of buttons:	Capacitive
Service buttons:	Lock-release, Answer, Silent (Privacy), Door open
No. of programmable buttons for additional functions:	5
Terminals:	L L - + CFP1 CFP2 S+ S- IN1 IN2
Removable terminals:	Yes



6601W

ICONA MONITOR, S2

HARDWARE FEATURES

Number of inputs:	2
-------------------	---

SETTINGS

Loudspeaker volume:	Yes
Ringtone volume:	Yes
Screen brightness:	Yes
Screen contrast:	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection degree:	IP30
Operating temperature (°K):	41 ÷ 104
Operating humidity (RH max - %):	25 ÷ 75
Environmental class:	I
Compliance and Certifications:	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener:	Yes
Self-ignition:	Yes
Intercom calls:	Yes
Actuator control:	Yes
Outside door call input:	Yes
Output for call repetition:	Yes
"Silent" mode (Privacy):	Yes
Door opening on call (Doctor):	Yes
Automatic answer (handsfree):	Yes
Door open signaling:	Yes
Customizable ringtone:	Yes
Sending alarm calls:	Yes

**6601W****ICONA MONITOR, S2**

ACCESSORIES

**6117**

FLUSH-MOUNTED BOX FOR PLANUX, SMART, ICONA MONITORS

The accessory can be used for the tilt-adjustment fitting of art. 6122. Dimensions: 132X132X50 mm.

**6118**

PLANUX, SMART, ICONA CLIPS FOR DRY LINED WALLS

Installation kit for plasterboard walls for Planux, Smart and Icona monitors.

**6617**

Flush-mounted box for plasterboard. Icona

Flush-mount box allowing mounting of Icona series monitors on plasterboard and/or cement walls. Dimensions: 129x129x50 mm

**6620**

WALL BRACKET FOR ICONA MONITOR

Wall bracket for Icona monitor. Colour: White. Dimensions: 136.6x141.6x13.8mm.

**6612A**

DESK BASE FOR ICONA MONITOR

Desk base installation accessory for Icona monitor. Dimensions 105x70x110mm.