



6722W

MINI HANDSFREE BM MONITOR, VIP



Handsfree colour monitor for VIP system. 4.3" / 16:9 colour screen. 480x272 pixel resolution. H264 video format. All the main functions and programming operations can be performed from a graphic menu that can be navigated using the function keys. Equipped with 8 soft-touch keys: audio activation key with LED to signal incoming calls, lock-release key with door open indicator LED, Privacy function key with Led indicating ringtone excluded and Doctor function enabled, 4 programmable keys and 1 menu access key. Equipped with 3 programmable inputs. Adjustable backlight brightness and key feedback volume. Powered by PoE as standard or from VIP Comelit switches and power supply units. Includes induction loop with T position for users wearing hearing aids and answerphone function. Dimensions: 4.53"x6.3"x0.87".

AWARDS





6722W

MINI HANDSFREE BM MONITOR, VIP

GENERAL DATA

Product height (inch):	6.3
Product width (inch):	4.53
Product depth (inch):	0.87
Product weight (oz):	1.19
Product color:	White RAL9003
Material:	Plastic, ABS
Wall mounting:	Yes
Desk base-mounted:	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

ViP:	Yes
------	-----

DISPLAY FEATURES

Size (inches):	4.3
Aspect Ratio:	16:9
Resolution (pixels):	480x272
OSD menu:	Yes

AUDIO FEATURES

Type:	Hands-free
Induction loop function:	Yes
Microphone:	6mm (ø), omnidirectional
Loudspeaker:	36mm (ø), 8 ohm, 1W

ELECTRICAL CHARACTERISTICS

Type of power supply:	PoE
PoE power supply:	Standard IEEE 802.3af, Comelit PoE (56VDC)
Stand-by absorption (W):	1.65
Maximum absorption (W):	2.53

HARDWARE FEATURES

Type of buttons:	Capacitive
Service buttons:	Lock-release, Answer, Silent (Privacy), Menu, Messages, Door open
No. of programmable buttons for additional functions:	4
Terminals:	- IN1 IN2 IN3
Number of inputs:	3
Communication ports:	RJ45 (Ethernet)



6722W

MINI HANDSFREE BM MONITOR, VIP

SETTINGS

Loudspeaker volume:	Yes
Ringtone volume:	Yes
Screen backlight:	Yes

NETWORK AND COMMUNICATION PROTOCOLS

Type of LAN network:	Ethernet 10/100 Mbit/s, IEEE 802.3, IEEE 802.3u (Fast Ethernet)
IP address assignment:	Auto IP, DHCP, Static

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection degree:	IP30
Operating temperature (°K):	41 ÷ 104
Operating humidity (RH max - %):	25 ÷ 75
Environmental class:	I
Compliance and Certifications:	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener:	Yes
Self-ignition:	Yes
Intercom calls:	Yes
Actuator control:	Yes
CPS call:	Yes
Outside door call input:	Yes
"Silent" mode (Privacy):	Yes
Video memory:	Yes
Door opening on call (Doctor):	Yes
Automatic answer (handsfree):	Yes
Door open signaling:	Yes
Call forwarding:	Yes
Multiple address:	Yes
Customizable ringtone:	Yes
Date/time display:	Yes
Sending alarm calls:	Yes
Sending e-mail on event:	Yes
Receiving VIP messages:	Yes
ViP anti-theft function:	Yes

**6722W****MINI HANDSFREE BM MONITOR, VIP**

ACCESSORIES

**6711WV**

ADAPTER PLATE FOR MINI HANDSFREE

Adapter plate to finish the installation of the Mini Handsfree monitor in case of replacement of flush-mounted or wall-mounted Planux, Smart and Icona monitors. White color. Dimensions: 170x220x3 mm.

**6720V**

Access. cables external passage for MINI HF. VIP

Wall bracket for ViP system hands-free Mini monitor; allows through-routing of external cables.

**6732V**

Desk base for hands-free Mini ViP monitor

Desk base for desktop conversion of ViP system hands-free Mini monitor. Complete with 1 x 2 metre cable with RJ45 connector to connect monitor terminals to the coupler or residential series socket.