

1/5 OVERVIEW



6742W





Handsfree colour monitor for ViP system. With integral Wi-Fi port and gateway for forwarding video entry phone calls to smartphones and tablets equipped with the Comelit app. 4.3" / 16:9 colour screen. 480x272 pixel resolution. H264 video format. All the main functions and programming operations can be performed from a graphic menu that can be navigated using the function keys. Equipped with 8 soft-touch keys: audio activation key with LED to signal incoming calls, lock-release key with door open indicator LED, Privacy function key with Led indicating ringtone excluded and Doctor function enabled, 4 programmable keys and 1 menu access key. Equipped with 3 programmable inputs. Adjustable backlight brightness and key feedback volume. Powered by PoE as standard or from ViP Comelit switches and power supply units. Includes induction loop with T position for users wearing hearing aids and answerphone function. Dimensions: 115x160x22mm.

AWARDS









6742W

MINI HANDSFREE BM WIFI MONITOR, VIP

GENERAL DATA	
Product height (inch):	6.3
Product width (inch):	4.53
Product depth (inch):	0.87
Product weight (oz):	0.95
Product color:	White RAL9003
Material:	Plastic, ABS
Wall mounting:	Yes
Desk base-mounted:	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

ViP: Yes

DISPLAY FEATURES	
Size (inches):	4.3
Aspect Ratio:	16:9
Resolution (pixels):	480x272
OSD menu:	Yes

AUDIO FEATURES	
Туре:	Hands-free
Induction loop function:	Yes
Microphone:	6mm (ø), omnidirectional
Loudspeaker:	36mm (ø), 8 ohm, 1W

ELECTRICAL CHARACTERISTICS	
Type of power supply:	PoE
PoE power supply:	Standard IEEE 802.3af, Comelit PoE (56VDC)
Stand-by absorption (W):	2.64
Maximum absorption (W):	3.52

HARDWARE FEATURES	
Type of buttons:	Capacitive
Service buttons:	Answer, Silent (Privacy), Menu, Messages, Door open
No. of programmable buttons for additional functions:	4
Terminals:	- IN1 IN2 IN3
Number of inputs:	3
Communication ports:	RJ45 (Ethernet)





6742W

MINI HANDSFREE BM WIFI MONITOR, VIP

SETTINGS	
Loudspeaker volume:	Yes
Ringtone volume:	Yes
Screen backlight:	Yes

NETWORK AND COMMUNICATION PROTOCOLS	
Type of LAN network:	Ethernet 10/100 Mbit/s, IEEE 802.3, IEEE 802.3u (Fast Ethernet)
Type of Wi-Fi connection:	IEEE 802.11 b/g/n, 2.4 Ghz, 13 channels
Encryption and authentication method supported:	OPEN WPA-PSK networks, TKIP WPA2-PSK, AES WEP 64 bits (5-digit
	ASCII or 10 hexadecimal codes), WEP 128 bits (13-digit ASCII or 26
	hexadecimal codes), WPS authentication (supported for WPA2-PSK)
IP address assignment:	Auto IP, DHCP, Static
IoT connection to Comelit Cloud:	Yes
Firmware update via Comelit Cloud:	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES	
IP protection degree:	IP30
Operating temperature (°K):	41 ÷ 104
Operating humidity (RH max - %):	25 ÷ 75
Environmental class:	I
Compliance and Certifications:	RoHS II - 2011/65/UE (EN 50581:2012), RED 2014/53/UE (EN
	60950-1:2006+A11:2009+A1:2010+A12:2011, +A2:2013, EN
	62311:2008, EN 61000-6-1:2007, EN 61000-6-3:2007 + A1:2011,
	ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300
	328 V2.1.1)

MAIN FUNCTIONS	
Compatibility with Comelit app:	Yes
Door opener:	Yes
Self-ignition:	Yes
Intercom calls:	Yes
Actuator control:	Yes
CPS call:	Yes
Outside door call input:	Yes
"Silent" mode (Privacy):	Yes
Video memory:	Yes
Door opening on call (Doctor):	Yes
Automatic answer (handsfree):	Yes



 $4/5 \mapsto$ function and general data

6742W

MINI HANDSFREE BM WIFI MONITOR, VIP

MAIN FUNCTIONS	
Door open signaling:	Yes
Call forwarding:	Yes
Multiple address:	Yes
Customizable ringtone:	Yes
Date/time display:	Yes
Sending alarm calls:	Yes
Sending e-mail on event:	Yes
Receiving ViP messages:	Yes
ViP anti-theft function:	Yes



6742W

MINI HANDSFREE BM WIFI MONITOR, VIP

ACCESSORIES



6711WV

ADAPTER PLATE FOR MINI HANDSFREE

Adapter plate to finish the installation of the Mini Handsfree monitor in case of replacement of flush-mounted or wall-mounted Planux, Smart and Icona monitors. White color. Dimensions: 170x220x3 mm.

6720V



Access. cables external passage for MINI HF. ViP

Wall bracket for ViP system hands-free Mini monitor; allows through-routing of external cables.

6732V



Desk base for hands-free Mini ViP monitor

Desk base for desktop conversion of ViP system hands-free Mini monitor. Complete with 1x 2 metre cable with RJ45 connector to connect monitor terminals to the coupler or residential series socket.